

# COMPACT & EFFICIENT

Made for smaller jobs or the rental industry, consider the performance and reliability of installing 1000 sq ft of R-19 cellulose in less than an hour or 1000 sq ft of R-19 fiberglass in less than 1.5 hours.

- There are two options available, the standard (28.5 in x 28.5 in x 38 in) or with hopper extension, which brings the height from 38 inches to 59.3 inches.
- Slide gate control provides users with cellulose drill and fills or dense fiberglass pack retrofit capabilities.
- Automatic chain tensioners and durable components provide minimal maintenance offering the lowest life-cycle costs.

## Specifications

- Weight - 142/194
- Outlet - 2.5 inch
- Power - 1 15 AMP (best w/1-20 AMP)
- Power Cord -12/3 x 100 foot
- Remote - Remote 100 ft wired



# BLO-K81018-13  
# BLO-K81018-17 (hopper extension)

## Warranty

- 12 Months for Components

*See the next page for more product specs.*



**CONTACT US  
FOR MORE INFO!**

[service-partners.com](http://service-partners.com)

**ASK ABOUT OUR  
E750 BLOWING  
MACHINE**

# PRODUCT SPEC CHART

		e2500	e2000	e1000	e750	e500
<b>DESCRIPTION</b>	Portability	Average	Average	Above Avg	Ultimate	Above Avg
	Weight (lbs)	459	416	239	174	142/194
<b>CAPACITY</b>	Hopper (cubic feet)	15	15	10	9	5.8/8
	Hopper Bag Capacity Cellulose	2 to 3	2 to 3	1	1 to 2	0.5
	Hopper Bag Capacity Fiberglass	.5 to 1	.5 to 1	.5 to .75	0.5	0.33
	Outlet (inches)	3	3	3	2.5	2.5
<b>PRODUCTION</b>	Blower - Single Stage	NA	NA	NA	•	No
	Blower - Two Stage	•	•	•	No	•
	Production Cellulose lbs/min	41 to 55	31 to 41	26 to 35	13 to 17	12 to 16
	Production Fiberglass lbs/min	15 to 20	12 to 15	7 to 10	5 to 7	3 to 4
	Install Time Cellulose R19 1000 sq ft	12 min	15 min	18 min	39 min	42 min
	Install Time Fiberglass R19 1000 sq ft	12 min	17 min	25 min	38 min	64 min
	Cellulose Dense Pack Retrofit	•	•	•	NA	•
	Fiberglass Dense Pack Retrofit	•	•	•	•	•
<b>FEATURES</b>	Seals - Urethane Casted (2-3X longer life)	•	•	•	•	•
	Stainless Steel Airlock Plates	•	•	•	•	•
	Quick Adjust Gate with pin setting	•	•	•	•	•
	Electrical: # of 115V circuits required to operate machine	1 - 15 Amp & 1 - 20 Amp; additional 1-15 Amp optional.	2 - 15 Amp; additional 1-15 Amp optional.	2 - 15 Amp	1-15 Amp	1-15 Amp (best with 1-20 Amp)
	Back-Flow Valve	•	•	•	NA	NA
	Slide Gate	•	•	•	•	•
	Handles	•	•	•	•	•
	Wheels	•	•	•	•	•
<b>REMOTES</b>	Remote - 150 ft wired	STD	Optional	Optional	NA	Optional
	Remote- 100 ft wired	Optional	STD	STD	NA	STD
	Wireless Remote w/jacket	Optional	Optional	Optional	STD	NA
	Power Cord	12/3 Twist Lock Qty = 3 @ 100'	12/3 Twist Lock Qty = 3 @ 100'	12/3 Twist Lock Qty = 2 @ 100'	14/3 Twist Lock Qty = 1 @ 50' with LED indicator	12/3 x 100'
<b>WARRANTY</b>	Warranty - 1 year	•	•	•	•	•
<b>FIELD READY</b>	Mark II Hose	150' 3"	150' 3"	100' 3"	100' 2.5"	100' 2.5"
	Metal Hose Connector	1	1	NA	NA	1
	Swivel Urethane Hose Connector	1	1	1	NA	NA
	Hose Clamps	5	5	3	3	3
	Quick Connect Hose Connections	NA	NA	NA	Yes	NA
	Quick Clean Inlet Air Filter	•	•	•	•	NA
	Unit Controls w/Visible Instructions	•	•	•	•	•