

GOT SMALL JOBS?

Need the perfect unit for small jobs or renting out? This two-piece design fits most vehicles, is durable and lightweight for maneuverability ease, with simple electrical needs of one 15 Amp 115 V circuit.

- Standard wireless remote speeds up set-up and tear down.
- Hinged shelf holds material, so you don't have to.
- Comes standard with a 14/3 - 50 ft twist lock power cord and 100 ft of 2.5-inch hose with quick connects, blowing up to 1000 lbs per hour of cellulose or 400 pounds per hour of fiberglass.
- Slide gate allows for applications in addition to attics.



BLO-50013-20

Specifications

- Weight - 174
- Outlet - 2.5 inch
- Power - 1 15 AMP
- Power Cord - 14/3 Twist Lock; 1 @ 50 foot (LED indicator)
- Remote - Wireless Remote w/jacket

Warranty

- 12 Months for Components

See the next page for more product specs.



**CONTACT US
FOR MORE INFO!**

service-partners.com

**ASK ABOUT OUR
E1000 BLOWING
MACHINE**

PRODUCT SPEC CHART

	e2500	e2000	e1000	e750	e500	
DESCRIPTION	Portability	Average	Average	Above Avg	Ultimate	Above Avg
	Weight (lbs)	459	416	239	174	142/194
CAPACITY	Hopper (cubic feet)	15	15	10	9	5.8/8
	Hopper Bag Capacity Cellulose	2 to 3	2 to 3	1	1 to 2	0.5
	Hopper Bag Capacity Fiberglass	.5 to 1	.5 to 1	.5 to .75	0.5	0.33
	Outlet (inches)	3	3	3	2.5	2.5
PRODUCTION	Blower - Single Stage	NA	NA	NA	•	No
	Blower - Two Stage	•	•	•	No	•
	Production Cellulose lbs/min	41 to 55	31 to 41	26 to 35	13 to 17	12 to 16
	Production Fiberglass lbs/min	15 to 20	12 to 15	7 to 10	5 to 7	3 to 4
	Install Time Cellulose R19 1000 sq ft	12 min	15 min	18 min	39 min	42 min
	Install Time Fiberglass R19 1000 sq ft	12 min	17 min	25 min	38 min	64 min
	Cellulose Dense Pack Retrofit	•	•	•	NA	•
	Fiberglass Dense Pack Retrofit	•	•	•	•	•
FEATURES	Seals - Urethane Casted (2-3X longer life)	•	•	•	•	•
	Stainless Steel Airlock Plates	•	•	•	•	•
	Quick Adjust Gate with pin setting	•	•	•	•	•
	Electrical: # of 115V circuits required to operate machine	1 - 15 Amp & 1 - 20 Amp; additional 1-15 Amp optional.	2 - 15 Amp; additional 1-15 Amp optional.	2 - 15 Amp	1-15 Amp	1-15 Amp (best with 1-20 Amp)
	Back-Flow Valve	•	•	•	NA	NA
	Slide Gate	•	•	•	•	•
	Handles	•	•	•	•	•
	Wheels	•	•	•	•	•
REMOTES	Remote - 150 ft wired	STD	Optional	Optional	NA	Optional
	Remote- 100 ft wired	Optional	STD	STD	NA	STD
	Wireless Remote w/jacket	Optional	Optional	Optional	STD	NA
	Power Cord	12/3 Twist Lock Qty = 3 @ 100'	12/3 Twist Lock Qty = 3 @ 100'	12/3 Twist Lock Qty = 2 @ 100'	14/3 Twist Lock Qty = 1 @ 50' with LED indicator	12/3 x 100'
WARRANTY	Warranty - 1 year	•	•	•	•	•
FIELD READY	Mark II Hose	150' 3"	150' 3"	100' 3"	100' 2.5"	100' 2.5"
	Metal Hose Connector	1	1	NA	NA	1
	Swivel Urethane Hose Connector	1	1	1	NA	NA
	Hose Clamps	5	5	3	3	3
	Quick Connect Hose Connections	NA	NA	NA	Yes	NA
	Quick Clean Inlet Air Filter	•	•	•	•	NA
	Unit Controls w/Visible Instructions	•	•	•	•	•