



HIGH CAPACITY TRUCK/TRAILER MOUNT MACHINES

 This truck/trailer mount machine features a dependable 23-27 hp Honda electric start gas motor.

Use with cellulose, fiberglass, and stonewall insulations.

Applications range from attics to BIBS,
 J.M. Spider Plus, & JetSpray Thermal Wall.

 Easily operable from descriptive panel, wired, or optional wireless remote.

 A generous loading platform and large hopper with precision feed agitator and dual shredders move 25-35 lbs of fiberglass per minute and 73-84 lbs for cellulose.


• The narrow width fits various vehicles, and the low height accommodates average installer reach.



See the next page for more product specs.

(GOWIRELESS LRT/HP remote)





PRODUCT SPEC CHART

Z		G3000	G5000
CAPACITY DESCRIPTION	Portability	Stationary	Stationary
		1015	
	Weight (lbs)		1500
	Hopper (cubic feet)	45	49
	Hopper Bag Capacity Fiberglass	3 to 4	2 to 3
	Hopper Bag Capacity Cellulose	7 to 9	5 to 6
	Outlet (inches)	3	4
ENGINE	Vanguard V-Twin	18 hp	NA
	Honda V-Twin	NA	23-27 hp
	Electric Starter	•	•
	Fuel Tank Size	6.95 quart	4 Gal
FEATURES	Chain Size	40	50
	Tensioner (Built-In)	•	•
	Dual Pulley	•	•
	Seals - Urethane Casted (2-3X longer life)	•	Belted Rubber
	Quick Access Airlock	Yes, slide-out	Yes, removable front section
	Quick Adjust Gate (w/ Handle)	•	•
	Blower Motor (oversized positive displacement)	•	•
	Back-Flow Valve	•	•
	Pressure Relief Valve	•	•
	Air Dump Valve	•	•
	Fresh Air Inlets	•	•
	Remote - 150 ft wired	•	•
	Wireless Remote	Available	Available
	Warranty 3 years - Engine 1 year - other components	•	•



SPV CONTACT US FOR MORE INFO!