

JUST RIGHT

The right size vacuum for recycling of spray applied insulation or removal on mid-size attic jobs.

- It works with a standard six-inch hose but can switch to a four-inch hose.
- The robust Vanguard 18 hp V-Twin electric start motor features easy-to-use controls, quiet exhaust, oversized shaft, hour meter, and generous gas tank with debris filter.
- The cannon-mount design with pivoting inlet & outlet gate is movable with a central lift point handle.
- Like the Turbovac, debris flows through the heavy 1/4 inch abrasive resistant steel shroud and past the 1/4 inch thick abrasive resistant impeller.



Part # TURBOVACECO

Specifications

- Weight – 248 pounds
- Inlet/Outlet – 6 inches w/optional 4 inch
- 10 inch Run Flat Tires
- Vanguard V-Twin Engine w/electric start
- 18 H.P.
- Fuel Tank – 6.95 Quart – Gasoline

Warranty

- Engine – 36 Months
- Components - 12 Months

See the next page for more product specs.

PRODUCT SPEC CHART

	turbovac	turbovac eco	
DESCRIPTION	Portability	wheelbarrow	cannon-mount
	Weight (lbs)	362	248
	Inlet /Outlet (inches)	6	6
	Optional Inlet	NA	4
ENGINE/MOTOR	Honda V-twin Engine w/electric start	27 HP Gross/22 HP Net	NA
	Vanguard V-twin Engine w/electric start	NA	18 HP
	Oil Alert - auto shut off	•	•
	Fuel Tank Size	4 Gal	6.95 quart
	Translucent Fuel Tank & Filters	•	NA
	Carb Compliant	•	•
	Hour Meter	•	•
	Extra Quiet Exhaust	•	•
	Shaft - Oversized	•	•
	Sealed Electric Motor	NA	NA
	Power Cord	NA	NA
Power Needs	NA	NA	
UPGRADED INTERNAL PARTS	Impellor - Oversized abrasive resistant	1/4 inch thick	1/4 inch thick
	Shroud - double thick abrasive resistant	1/4 inch thick (wear section)	1/4 inch thick (wear section)
	Wheels - Run Flat	10 inch	10 inch
	Powder Coated Steel Body	•	•
	Pivoting Inlet & Outlet Gate	•	•
	Optional Dryer Plug Conversion	NA	NA
	Warranty Info		
	Warranty 3 years - Engines	•	•
	Warranty 1 year - other components	•	•



**CONTACT US
FOR MORE INFO!**

service-partners.com