

PORTABLE, DURABLE, LIGHTWEIGHT & RUST-FREE

- Just starting with attic fills and dense pack?
Consider this machine blowing 26-35 lbs/min of cellulose and 7-10 lbs/minute of fiberglass.
- Two-stage blower w/infinity brush technology and one-way valve provide high volume and longer life.
- Requiring two 115V -15 amps circuits, the urethane airlock seals and stainless steel airlock plates provide higher pressure and increased production rates with less maintenance.

Specifications

- Weight - 239
- Outlet - 3 inch
- Power - 2 - 15 AMP
- Power Cord -12/3 Twist Lock; 3 @ 100 foot
- Remote - 100 foot wired

Warranty

- 12 Months for Components



JDE Part# BLO-95000-00 (turbofiberz e1000)

JDE Part # BLO-95000-10 (turbofiberz e1000 GOWIRELESS)

*See the next page for
more product specs.*

PRODUCT SPEC CHART

	e2500	e2000	e1000	e750	e500	
DESCRIPTION	Portability	Average	Average	Above Avg	Ultimate	Above Avg
	Weight (lbs)	488	478	239	174	142/194
CAPACITY	Hopper (cubic feet)	15	15	10	9	6.8/9.5
	Hopper Bag Capacity Cellulose	2 to 3	2 to 3	1	1 to 2	0.5
	Hopper Bag Capacity Fiberglass	.5 to 1	.5 to 1	.5 to .75	0.5	0.33
	Outlet (inches)	3	3	3	2.5	2.5
PRODUCTION	Blower - Single Stage	NA	NA	NA	•	No
	Blower - Two Stage	•	•	•	No	•
	Production Cellulose lbs/min	41 to 55	31 to 41	26 to 35	13 to 17	12 to 16
	Production Fiberglass lbs/min	15 to 20	12 to 15	7 to 10	5 to 7	3 to 4
	Install Time Cellulose R19 1000 sq ft	12 min	15 min	18 min	39 min	42 min
	Install Time Fiberglass R19 1000 sq ft	12 min	17 min	25 min	38 min	64 min
	Cellulose Dense Pack Retrofit	•	•	•	NA	•
	Fiberglass Dense Pack Retrofit	•	•	•	•	•
FEATURES	Seals - Urethane Casted (2-3X longer life)	•	•	•	•	•
	Stainless Steel Airlock Plates	•	•	•	•	•
	Quick Adjust Gate with pin setting	•	•	•	•	•
	Electrical: # of 115V circuits required to operate machine	1 - 15 Amp & 1 - 20 Amp; additional 1-15 Amp optional.	2 - 15 Amp; additional 1-15 Amp optional.	2 - 15 Amp	1-15 Amp	1-15 Amp (best with 1-20 Amp)
	Back-Flow Valve	•	•	•	NA	NA
	Slide Gate	•	•	•	•	•
	Handles	•	•	•	•	•
	Wheels	•	•	•	•	•
REMOTES	Remote - 150 ft wired	STD	Optional	Optional	NA	Optional
	Remote - 100 ft wired	Optional	STD	STD	NA	STD
	Wireless Remote w/jacket	Optional	Optional	Optional	STD	NA
	Power Cord	12/3 Twist Lock Qty = 3 @ 100'	12/3 Twist Lock Qty = 3 @ 100'	12/3 Twist Lock Qty = 2 @ 100'	14/3 Twist Lock Qty = 1 @ 50' with LED indicator	12/3 x 100'
WARRANTY	Warranty - 1 year	•	•	•	•	•
FIELD READY	Mark II Hose	150' 3"	150' 3"	100' 3"	100' 2.5"	100' 2.5"
	Metal Hose Connector	1	1	NA	NA	1
	Swivel Urethane Hose Connector	1	1	1	NA	NA
	Hose Clamps	5	5	3	3	3
	Quick Connect Hose Connections	NA	NA	NA	Yes	NA
	Quick Clean Inlet Air Filter	•	•	•	•	NA
	Unit Controls w/Visible Instructions	•	•	•	•	•