

# HIGH CAPACITY TRUCK/TRAILER MOUNT MACHINES

- This truck/trailer mount machine features a dependable 23-27 hp Honda electric start gas motor.
- Use with cellulose, fiberglass, and stone wool insulations.
- Applications range - attics.
- Easily operable from descriptive panel, wired, or optional wireless remote.
- A generous loading platform and large hopper with precision feed agitator and dual shredders move 25-35 lbs of fiberglass per minute and 73-84 lbs for cellulose.
- The narrow width fits various vehicles, and the low height accommodates average installer reach.



# BLO-SS5000  
# BLO-SS5000-W  
(GOWIRELESS LRT/HP remote)

See the next page for  
more product specs.



## CONTACT US TODAY!

Name \_\_\_\_\_  
Phone \_\_\_\_\_  
Email \_\_\_\_\_

ASK ABOUT  
OUR TURBOVAC  
MACHINES!

# PRODUCT SPEC CHART

	G3000	G5000	G7000
<b>DESCRIPTION</b>	Portability	Stationary	Stationary
	Weight (lbs)	1015	1500
	Hopper (cubic feet)	45	49
<b>PRODUCTION</b>	Hopper Bag Capacity Fiberglass	3 to 4	2 to 3
	Hopper Bag Capacity Cellulose	7 to 9	5 to 6
	Outlet (inches)	3	4
	Install Time Cellulose R19 1000 sq ft	11 min	8 min
	Install Time Fiberglass R19 1000 sq ft	11 min	8 min
<b>ENGINE</b>	Vanguard V-Twin Electric Starter	18 hp	NA
	Honda V-Twin Electric Starter	NA	23-27 hp
	Honda V-Twin Electronic Fuel Injection	NA	NA
	Kubota z602 Diesel	NA	NA
	Fuel Tank Size	6.95 quart	4 Gal
<b>FEATURES</b>	Chain Size	40	50
	Tensioner (Built-In)	•	•
	Dual Pulley	•	•
	Seals - Urethane Casted (2-3X longer life)	•	Belted Rubber
	Quick Access Airlock	Yes, slide-out	Yes, removable front section
	Quick Adjust Gate (w/ Handle)	•	•
	Blower Motor (oversized positive displacement)	•	•
	Back-Flow Valve	•	•
	Pressure Relief Valve	•	•
	Air Dump Valve	•	•
	Fresh Air Inlets	•	•
	Remote - 150 ft wired	•	•
	Wireless Remote	Available	Available
	Warranty		
	3 years - Engine	•	•
1 year - other components			



**CONTACT US  
FOR MORE INFO!**

[service-partners.com](http://service-partners.com)