

HIGH CAPACITY TRUCK/TRAILER MOUNT MACHINES

- This truck/trailer mount machine features a dependable POWERED by Honda electric start iGX700 V-Twin or Optional a Industrial Grade Kubota z602.
- Use with cellulose, fiberglass, and stone wool insulations.
- Applications range from attics to BIBS, Dense-Pack, Damp-Spray Cellulose, J.M. Spider Plus, JetSpray Thermal Wall or the newest Wood Fiber loose fill.
- Control this Big Machine with ease from the simplistic control panel, you can go wired, or optional wireless remote.
- A generous loading platform and large hopper (68 cu. ft.) with precision feed agitator and dual shredders move 30-39 lbs of fiberglass per minute and 75-95 lbs for cellulose.
- Maintenance minimized with Easy Access Airlock Seals, Grease Zerk Station, Heavy Duty Gearbox, Dual Belts w/Automatic Tensioner.



SKU: BLO-TFG7000 (Honda Gas v-Twin)

SKU: BLO-TFG7000GW (Honda Gas V-Twin GOWIRELESS LRT/HP remote)

SKU: BLO-TFD7000GW (Kubota Diesel GOWIRELESS LRT/HP remote)

See the next page for
more product specs.



CONTACT US TODAY!

Name _____
Phone _____
Email _____

**ASK ABOUT
OUR TURBOVAC
MACHINES!**

PRODUCT SPEC CHART

	G3000	G5000	G7000	
DESCRIPTION	Portability	Stationary	Stationary	Stationary
	Weight (lbs)	1015	1500	1750
	Hopper (cubic feet)	45	49	68
PRODUCTION	Hopper Bag Capacity Fiberglass	3 to 4	2 to 3	4 to 5
	Hopper Bag Capacity Cellulose	7 to 9	5 to 6	11 to 12
	Outlet (inches)	3	4	4
	Install Time Cellulose R19 1000 sq ft	11 min	8 min	6 min
	Install Time Fiberglass R19 1000 sq ft	11 min	8 min	6 min
ENGINE	Vanguard V-Twin Electric Starter	18 hp	NA	NA
	Honda V-Twin Electric Starter	NA	23-27 hp	NA
	Honda V-Twin Electronic Fuel Injection	NA	NA	•
	Kubota z602 Diesel	NA	NA	•
	Fuel Tank Size	6.95 quart	4 Gal	5 Gal
FEATURES	Chain Size	40	50	50
	Tensioner (Built-In)	•	•	•
	Dual Pulley	•	•	•
	Seals - Urethane Casted (2-3X longer life)	•	Belted Rubber	Belted Rubber
	Quick Access Airlock	Yes, slide-out	Yes, removable front section	Yes, removable front section
	Quick Adjust Gate (w/ Handle)	•	•	•
	Blower Motor (oversized positive displacement)	•	•	•
	Back-Flow Valve	•	•	•
	Pressure Relief Valve	•	•	•
	Air Dump Valve	•	•	•
	Fresh Air Inlets	•	•	•
	Remote - 150 ft wired	•	•	•
	Wireless Remote	Available	Available	Available
	Warranty			
	3 years - Engine	•	•	•
1 year - other components				



**CONTACT US
FOR MORE INFO!**

service-partners.com