



LONG LASTING VAC

Engineered for high productivity, and built-to-last for high value generation.

- Minimized Engine Stress high production impeller positioned on its own shaft and activated by a centrifugal clutch.
- A built in vacSHIELD to capture foreign objects from damaging the vacuum impeller, shroud or engine and exiting at high speeds.
- Vanguard 23 Hp V-Twin
- Like the Turbovac, debris flows through the heavy 1/4 inch abrasive resistant steel shroud and past the 1/4 inch thick abrasive resistant impeller.



Specifications

- Weight-435 pounds
- Inlet/Outlet-6 inches w/optional 8 inch
- 10 inch Run Flat Tires
- Vanguard V-Twin Engine w/electric start
- 23 hp
- Fuel Tank 5 Gallon Gasoline

Warranty

- Engine 36 Months
- Components 12 Months

See the next page for more product specs.







PRODUCT SPEC CHART

Z		turbovac	turbovac endura	turbovacXL
DESCRIPTION	Portability	wheelbarrow	cannon-mount	wheelbarrow
	Weight (lbs)	362	435	362
	Inlet /Outlet (inches)	6	6	6
	Optional Inlet	NA	8	NA
ENGINE/MOTOR	Honda V-twin Engine w/electric start	27 HP Gross/22 HP Net	NA	27 HP Gross/22 HP Net
	Vanguard V-twin Engine w/electric start	NA	23 HP	NA
	Oil Alert - auto shut off	•	•	•
	Fuel Tank Size	4 Gal	5 Gal	4 Gal
	Translucent Fuel Tank & Filters	•	NA	•
	Carb Compliant	•	•	•
	Hour Meter	•	•	•
	Extra Quiet Exhaust	•	•	•
	Shaft - Oversized	•	•	•
	Sealed Electric Motor	NA	NA	NA
	Power Cord	NA	NA	NA
	Power Needs	NA	NA	NA
UPGRADED INTERNAL PARTS	Impellor - Oversized abrasive resistant	1/4 inch thick	1/4 inch thick	1/4 inch thick
	Shroud - double thick abrasive resistant	1/4 inch thick (wear section)	1/4 inch thick (wear section)	1/4 inch thick (wear section)
	Wheels - Run Flat	10 inch	10 inch	10 inch
	Powder Coated Steel Body	•	•	•
	Pivoting Inlet & Outlet Gate	•	•	•
	Optional Dryer Plug Conversion	NA	NA	NA
	Warranty Info			
	Warranty 3 years - Engines	•	•	•
	Warranty 1 year - other components	•	•	•



